




DGG 29 - Combination Drill Sharpener



Multi-Function Machine for Standard Drill Points
Split Point Drills
and
Multi-Facet Drill Points







Accurate And Fast - Get A Perfect Drill Bit Instantly

Peerless Superior Function, Stable and Precise

Quality Assurance Easy to Operate, Stable Quality

High Efficiency High Quality Grinding Wheel, Great Grinding Results


Considerable Design Invisible Tool Box, Refined And Pleasant Use

Mobility Portable by Design

Multi Function Drill Sharpener



Large, High Quality Electro Plated Grinding Wheels Require no Dressing And Guarantee Stable Results.



Technical Specifications:	DGS 29 Drill Sharpener			
Drill Point Type	2 Flute Drills with Nachi ES-Point*		2 Flute Drills with Standard Point	
Drill Bit Diameter Range *	12 to 26 mm	1/2 to 1 inch	12 to 26 mm	1/2 to 1 inch
Point Angle Range	118 to 140 degree		90 to 140 degree	
Web Thinning / Split-Point	X-type modified		X-type	
Grinding Wheel Size	125 mm	5 inch	125 mm	5 inch
Grinding Wheel Type	Electro Plated CBN #200, total of 2 (ea)			
Spindle Speed	3280 rpm			
Collet Size	ER 32			
Power Supply	Single Phase, 120V, 50/60 cycle. (Option: 220V-240V, 50cycle)			
Grinder Size Length x Width x Heights	430 x 225 x 270 mm		17 x 8 3/4 x 10 5/8 inch	
Grinder Weight approximately	32 kg		70.5 lbs	
Standard Accessories (included)	15 Each ER32 Collets in 1mm (0.040") Steps , Grinding Chuck Assembly, Metal Shim Set for Web Thinning Adjustment, US-Power Cord 2 Each Allen Wrench, 3mm and 5mm Size, Operating Manual (English)			
Available Options	Electro Plated Diamond Wheel, SDC # 200			
* Multi Facet, Multi Rake Point	Set of Intermediate Collets			

^{*} Drill Range extended, optional a.) to 3mm/ 0.12" or b.).to 34mm / 1-5/16" at request

1. Standard Grinding Ports on right side.



Sharpen Drill Points from 90 to 140 deg.
Split-Point with
X-thinning







2. Grinding Ports on left side. (Steps for ES-type points.)



Sharpen Multi-Facet Point Geometries from 118 to 140 deg. (Nachi SG-ES Point)





Grinding Chuck clamps with tool collets for precise tip concentricity

3. Standard Supplied Accessories:



Tool Collet Set in 1mm / 0.040" steps for drill range specified. Precise centering of drill bits for grinding.



Optional Accessories:



Diamond Plated Grinding Wheels for Carbide Drills



Collet Sets

Intermediate collet sizes, or special collet set to improve concentric clamping, e.g. for high speed drill use.



SharperDrills"Ltd.

9674 Colerain Ave, Suite 221 Cincinnati, Ohio 45251 Phone: +1(513)328-5041 www.sharperdrills.com